



Corroseal

CORROGUARD MASTIC STRIP

DESCRIPTION:

A permanently plastic mastic, moulded by hand, based on bitumen and rubber.

PRIMER:

Apply Corroguard Primer prior to application of mastic strip.

USES:

To fill holes and cracks in factory applied polyethylene coatings for pipes and fittings. Contours around welds, seams to eliminate any sharp edges prior to wrapping. Apply Corroguard Primer prior to application of mastic strip.

TECHNICAL DATA

THICKNESS	2mm
COLOUR	Black
SOLIDS CONTENT	100% Rubberised Bitumen
SPECIFIC GRAVITY	1.1
HARDNESS	70 00 durometer
BREAKDOWN VOLTAGE	10 kV
AVAILABLE SIZES	50mm x 10m and 100mm x 10m

Disclaimer:

This information is presented as accurate and correct in good faith, to assist the user in specification and application. No warranty is expressed or implied. No liability is assumed. Product specifications are subject to change without notice.

Corroseal Coatings Pty. Ltd. ABN 93 070 304 031 Unit 3/6 Blackmore Road Smeaton Grange P O Box 695 Narellan NSW 2567

Phone: 61 2 4648 1644 Fax: 61 2 4648 1655 E-mail: info@corroseal.com.au Web: www.corroseal.com.au