



Corroseal

CORROGUARD PRIMER

DESCRIPTION:

Brush or spray applied bitumen based primer for application to clean metal before applying Corroguard Tape.

COMPOSITION:

High softening point bitumen in liquid hydrocarbon conditions.

CHARACTERISTICS:

Good penetration and healing properties. Resists degradation in aggressive industrial and climatic conditions.

APPLICATION:

Apply a then even coat to clean surface and shop coatings allow to tack dry (10 to 20 mins) before wrapping. Clean with white spirit.

TECHNICAL DATA

APPLICATION TEMPERATURE RANGE	0°C to 55.°C
SERVICE MAXIMUM	60°C
FLASHPOINT	32°C
SPECIFIC GRAVITY	0.91 approximately
COVERAGE	9 – 11m ² / litre average
PACKAGE	4 Litre Tins (4 per carton)

Disclaimer:

This information is presented as accurate and correct in good faith, to assist the user in specification and application. No warranty is expressed or implied. No liability is assumed. Product specifications are subject to change without notice.

Corroseal Coatings Pty. Ltd. ABN 93 070 304 031 Unit 3/6 Blackmore Road Smeaton Grange P O Box 695 Narellan NSW 2567

Phone: 61 2 4648 1644 Fax: 61 2 4648 1655 E-mail: info@corroseal.com.au Web: www.corroseal.com.au