



**Corroseal**

## **CORROSEAL MASTIC**

**DESCRIPTION:** Petrolatum based filling compound composed of refined saturated petroleum hydrocarbons, inert fillers, cellulose and synthetic fibres, which will not crack or harden and remains permanently flexible.

Used as a void filling and sealing material for profiling around wharf piles and other irregular shapes to improve contours for subsequent tape wrapping.

Highly resistant to minerals, acids, alkalis, salts and the marine environment.

### **TECHNICAL DATA**

SPECIFIC GRAVITY	Approximately 1.1
DENSITY	3kg = 0.010m <sup>3</sup>
TEMPERATURE RANGE	5.°C to 45.°C
PACKAGING	3kg Block

**Disclaimer:**

This information is presented as accurate and correct in good faith, to assist the user in specification and application. No warranty is expressed or implied. No liability is assumed. Product specifications are subject to change without notice.

Corroseal Coatings Pty. Ltd. ABN 93 070 304 031 Unit 3/6 Blackmore Road Smeaton Grange P O Box 695 Narellan NSW 2567

Phone: 61 2 4648 1644 Fax: 61 2 4648 1655 E-mail: [info@corroseal.com.au](mailto:info@corroseal.com.au) Web: [www.corroseal.com.au](http://www.corroseal.com.au)