



**Corroseal**

**H.D./PVC OUTERWRAP**

**DESCRIPTION:** A non-rigid Polyvinyl Chloride Tape, highly impermeable to water, water vapour and air exhibits.

Excellent long term resistance to UV, sea water, alkalis acids, oils and bacteria.

**TECHNICAL DATA**

<b>SERVICE TEMPERATURE</b>	18°C to 80°C
<b>APPLICATION TEMPERATURE</b>	0°C to 60°C
<b>TENSILE STRENGTH</b>	89N per mm Width ASTM-D-1000 (Min)
<b>ELONGATION</b>	200% ASTM-D-1000 (Min)
<b>ADHESION TO STEEL</b>	424g per 25mm Width ASTM-D-1000 (Min)
<b>ADHESION TO BACKING</b>	396g per 25mm Width ASTM-D-1000 (Min)
<b>DIELECTRIC STRENGTH</b>	9000 Volts
<b>VOLUME RESISTIVITY</b>	Over 10 Megalin ASTM-D-1000
<b>LENGTH</b>	30m Roll
<b>WIDTH AVAILABLE</b>	50mm, 100mm and 150mm
<b>COLOUR</b>	Black

Disclaimer:

This information is presented as accurate and correct in good faith, to assist the user in specification and application. No warranty is expressed or implied. No liability is assumed.

Product specifications are subject to change without notice.

Corroseal Coatings Pty. Ltd. ABN 93 070 304 031 Unit 3/6 Blackmore Road Smeaton Grange P O Box 695 Narellan NSW 2567

Phone: 61 2 4648 1644 Fax: 61 2 4648 1655 E-mail: [info@corroseal.com.au](mailto:info@corroseal.com.au) Web: [www.corroseal.com.au](http://www.corroseal.com.au)